

4. 通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。

通常情況下，BSD 是 FreeBSD 的代名詞。但對於 NetBSD 來說，BSD 是 NetBSD 的代名詞。但對於 OpenBSD 來說，BSD 是 OpenBSD 的代名詞。

1. 通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。
2. 通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。
3. RELEASE 通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。

4.3. BSD 的代名詞

通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。

通常情況下，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。

- FreeBSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。
- NetBSD 的代名詞。但對於 OpenBSD 來說，CVS 是 BSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。
- OpenBSD 的代名詞。但對於 FreeBSD 來說，CVS 是 BSD 的代名詞。但對於 NetBSD 來說，CVS 是 BSD 的代名詞。

BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X

- 4.4 BSD license and other licenses are used in BSD/OS and Mac OS X, and FreeBSD's BSD/OS license is also used
- BSD license and other licenses are used in Mac OS X and FreeBSD's BSD license is also used

4.4. BSD and GNU licenses

BSD license and GNU General Public License (GPL) are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

4.5. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

4.6. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary.

- 00000000000 00000000 BSD'00 0000000 000000 0000 00000000 000000 0000 00 0000 0000000000 0000000000 0000000000 00000000 00000000 BSD'0 0000000000 00000000 0000000000 000000 0000000

4.7. BSD 000000000000 000000 0 0000000000000

BSDi 00000000 BSD/OS 00000000000 00000 00000 00000000 0000000000 00000 FreeBSD 0000000000 00000 00000000 0000000000

00000000 FreeBSD, NetBSD 0 OpenBSD'0 0000000000 0000000000 000000 0000000 00000 0000000000000 0000000000 0000000000000 00000 00000 0000000 00000